

» V Panel Express «



Industrial Panel PC

- » High performance with embedded multi-core processor technology up to Intel® Core™ Duo processors
- » Ideal for running real time control and visualization simultaneously on one system or high-end rugged computing applications
- » Fanless cooling at maximum processor performance
- » Scalable display size: 12.1", 15", 17" and 19"

V Panel Express

Industrial Panel PC

The new V Panel Express line based on ETXexpress / COM Express technology offers supreme computing performance at low power consumption.

The integrated innovative cooling concept realizes a passive and fanless cooling for highest processor performance up to Intel® Core™ Duo processor technology. This allows critical and highly complex realtime applications to run on one computer almost twice the performance. The V Panel Express is ideal for running real time control and visualization simultaneously whereas previously these applications had to be run on two or more dedicated systems.

With a variety of interface options the V Panel Express easily adapts to customer specific requirements. The V Panel Express series systems are COM-based systems, compact, high performance human machine interfaces for tough industrial demands. Optimal shock, vibration and temperature resistance, as well as resistance against environments with increased electromagnetic interference are standard.

Technical Information

	121	150	170	190
Display	12.1" TFT	15.0" TFT	17.0" TFT	19.0" TFT
Resolution	800x600	1024x768	1280x1024	1280x1024
Brightness	350cd/m ²	250cd/m ²	250cd/m ²	250cd/m ²
Touch Screen	Resistive analog	Resistive analog	Resistive analog	Resistive analog
Weight	ca. 7.9 kg	ca. 8.9 kg	ca. 10.8 kg	ca. 13.2 kg
Dimensions (HxWxD)	312x380x163 mm	354x450x163 mm	399x461x168 mm	426x516x165 mm
Processor	up to Intel® Core™ Duo T2500			
RAM	up to 2 GByte			
I/O Standard	5x USB (1x front, 4x rear side), 1x LAN 10/100, 1x LAN 100/1000, 2x RS232, 1x DVI-I			
Free Slots	2x PCI			
Internal Drives	optional 2x Compact Flash, 2x SATA HDD			
Power Supply	24 VDC			
Cooling	Fanless			
EMC	US:FCC47 CFR PART15; Class A level CE:EN61000-6-2; EN55022/A (CISPR22)			
Certifications	CE, cULus			
Protection Class	IP65 front (NEMA 250 Type 12 and 13)			
Altitude	Operating: 10000 ft (3.048m); Storage: 15000 ft (4.622m)			
Shock DIN EN 60068-2-27	Operating: 15 g 11 ms duration / Storage: 30G, 11ms duration (half-sinus)			
Vibration DIN EN 60068-2-6	Operating: 10-500 Hz: 1G/3 axis / Storage: 10-500 Hz: 2G/3 axis			
Temperature / Humidity	Operating: 0°C to +50° / 20 to 85% non condensing Storage: -20°C to +60° / 5 to 95% non condensing			
MTBF	> 40000 h (excluding the Backlight Tube)			
Verified OS	Windows XP (Embedded), Linux (Embedded)			
RoHS compliant	yes			

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China
Tel.: + 86 10 63751188
Fax: + 86 10 83682438
info@kontron.cn

